

**PRODUCT DATA SHEET F-LON® 5010 Series**

**F-LON® 5010** is an excellent **Low Friction** coating. It also exhibits high level of hardness and heat dissipation.

**F-LON® 5010** is a patented Fluoropolymer coating applied in a single coat, exhibiting the following properties:

- Low cure temperature.
- Good colour stability.
- Easy application techniques.
- Good stain resistance.
- Good chemical resistance against a range of chemicals.

**F-LON® 5010** was developed for applications which:

- Are required to operate at elevated temperatures.
- Need excellent adhesion to most substrates with minimal surface preparation.
- Require an economical, durable, easy clean finish.

**F-LON® 5010 Series**

<b>Recommended Dry Film Thickness</b>	20 +/- 5 microns on flat plates 30-35 microns on round parts
<b>Substrates</b>	Any metallic substrate.
<b>Pre-treatment</b>	Phosphate, gritblast, degrease or passivation.
<b>Application method</b>	Hand spray or automatic spray line.
<b>Curing schedule</b>	+180 °C to +260 °C
<b>Operating Temperature</b>	-195 °C to +260 °C
<b>Colours available</b>	All colours, except white and light pastel shades, technically possible.
<b>Typical applications</b>	Examples of successful applications include rotary actuators, carburettors, bearings, any mating surfaces which require lubrication.
<b>Other properties</b>	Cryogenic stability Heat resistance Wear/Abrasion resistance Non- stick

*This product data sheet is based on the best information currently available and is offered to users in good faith but without offering or implying a warranty that such information is correct or has not been amended. Nor may it be assumed that patents, copyrights or design registrations concerning systems referred to herein may be ignored.*

